

POXI-ROCK II® - PERMERAL II® - CRACK 'N PATCH® - RESN-X II®

WHAT DOES IT TAKE...

to protect your new floor, or restore your eroded mess to better than new? *Find out why industry uses ROCK-TRED again, again..., and again.*



Please send additional information. I want to learn more.

Our floor is new existing concrete.

Cracked Lin. Ft.

Worn From Slippery

Chemically Eroded From

Damage is: Mild Severe Anticipated

Depth of Abrasion or Erosion (Circle): 1/32 1/16 1/8 1/4 Over 1/4 Inch

Size of Area Sq. Ft. Use For

NAME

800-762-8733

TITLE

COMPANY

**Over 50 Years of
Consistent Quality In
Products and Service
Backed by Our
Rock-Solid Guarantee!**

ADDRESS

CITY STATE ZIP

PHONE NO. FAX NO.

PLEASE CALL - BEST TIME: am/pm

Flooring the U.S.A. with a safer environment since 1939®



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD
FIRST CLASS PERMIT NO. 413 SKOKIE, IL.
POSTAGE WILL BE PAID BY ADDRESSEE



ROCK-TRED CORP
7440 N. St. Louis Avenue
Skokie, IL 60076-9811

